

INNERLINER SEALER ONYX+

Revision date: 22.11.2021

Product code: 12548-0011

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

INNERLINER SEALER ONYX+

Art.-No.

60730-67

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

adhesive

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: Street: Place: Telephone: Internet:	Schrader s.a.s. B.P. 29 - 48 rue de Salins F-25301 PONTARLIER Cedex +33 (0) 381.38.56.56 www.schrader-pacific.fr
Responsible Department:	Responsible for the safety data sheet: sds@gbk-ingelheim.de
Supplier	
Company name:	Schrader SPD Unit 1 Albion buildings
Street:	Kingfield road
Place:	Coventry, Cv1 4ng
Telephone:	+44 (0)2476 550880
e-mail:	info@schrader-pacific.co.uk
<u>1.4. Emergency telephone</u> number:	INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a) In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Hazard Statements: Highly flammable liquid and vapour. Causes skin irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

Danger

2.2. Label elements

Pictograms:

GB CLP Regulation

Hazard components for labelling Naphtha (petroleum)

Signal word:



Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.



INNERLINER SEALER ONYX+

Revision date: 22.11.2021

Product code: 12548-0011

Page 2 of 11

H411

Toxic to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 P273	Call a POISON CENTER/doctor if you feel unwell. Avoid release to the environment.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Preparation solved in petroleum spirit

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
64742-49-0	Naphtha (petroleum) [Hydrocart n-hexane]	oons, C6-C7, n-alkanes, iso-alkar	nes, cyclic compounds, < 3%	< 50 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT H411	SE 3, Asp. Tox. 1, Aquatic Chror	nic 2; H225 H315 H336 H304	
64742-49-0	Naphtha (petroleum) [Hydrocart	oons, C6, isoalkanes, < 3% n-hex	(ane]	< 20 %
	931-254-9		01-2119484651-34	
	Flam. Liq. 2, Skin Irrit. 2, STOT H411	SE 3, Asp. Tox. 1, Aquatic Chror	nic 2; H225 H315 H336 H304	
1314-13-2	Zinc oxide			< 1 %
	215-222-5	030-013-00-7	01-2119463881-32	
	Aquatic Acute 1, Aquatic Chroni	c 1; H400 H410	•	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc	Limits, M-factors and ATE	
1314-13-2	215-222-5	Zinc oxide	< 1 %
	oral: LD50 = 3	> 5000 mg/kg	

Further Information

According to note P to the regulation (EC) no. 1272/2008, "Naphta (petroleum)" is not to be classified as "carcinogenic" or "mutagen" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.



INNERLINER SEALER ONYX+

Revision date: 22.11.2021

Product code: 12548-0011

Page 3 of 11

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately. In the event of persistent symptoms receive medical treatment. Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours. Seek medical treatment immediately.

After contact with skin

Wash off with soap and plenty of water. Treat subsequently with skin cream. Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Summon a doctor immediately.

After ingestion

Do not induce vomiting. Summon a doctor immediately. Induce vomiting only upon the advice of a physician. Attention. Beware, danger of aspiration.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation. May cause drowsiness or dizziness. Attention. Beware, danger of aspiration.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO2), water-spray.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Fire may produce:

Carbon monoxide (CO), carbon dioxide (CO2) and sulphur oxides (SOx)

5.3. Advice for firefighters

Use breathing apparatus with independent air supply. Protective suit.

Additional information

Vapours are heavier than air and spread along ground.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures



INNERLINER SEALER ONYX+

Revision date: 22.11.2021

Product code: 12548-0011

Page 4 of 11

General advice

Ensure adequate ventilation. Remove persons to safety. Keep away sources of ignition.

For non-emergency personnel

In case of vapour formation use respirator. Avoid contact with skin, eyes and clothing.

For emergency responders

In case of vapour formation use respirator. Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

6.3. Methods and material for containment and cleaning up

For containment

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder). Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8). Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed. Vapours are heavier than air and spread along ground. Use only in thoroughly ventilated areas.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition. Do not smoke. Take precautionary measures against static discharges.

Use only explosion-proof equipment.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place. Pay attention to anti-explosion rules.

Hints on joint storage

Incompatible with oxidizing agents.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



according to UK REACH Regulation

INNERLINER SEALER ONYX+

Revision date: 22.11.2021

Product code: 12548-0011

Page 5 of 11

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
1333-86-4	Carbon black	-	3.5		TWA (8 h)	WEL
		-	7		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Treat subsequently with skin cream.

Avoid contact with skin, eyes and clothing.

Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).

Hand protection

Protective gloves resistant to chemicals made off nitrile, Minimum coat thickness 0.4 mm, Permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril 735> made by www.kcl.de. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Solvent-resistant apron (EN 467).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Odour:Hydrocarbon-likeTest methodpH-Value:n.d.Changes in the physical staten.d.Melting point/freezing point:n.d.Boiling point or initial boiling point and60 - 95 °Cboiling range:n.a.Sublimation point:n.a.Softening point:n.d.Flash point:- 24 °CDIN EN ISO 3679
pH-Value:n.d.Changes in the physical stateMelting point/freezing point:n.d.Boiling point or initial boiling point and boiling range:60 - 95 °CSublimation point:n.a.Softening point:n.d.
Changes in the physical stateMelting point/freezing point:n.d.Boiling point or initial boiling point and boiling range: $60 - 95 \ ^{\circ}C$ Sublimation point:n.a.Softening point:n.d.
Melting point/freezing point:n.d.Boiling point or initial boiling point and boiling range:60 - 95 °CSublimation point:n.a.Softening point:n.d.
Boiling point or initial boiling point and boiling range: Sublimation point:60 - 95 °C n.a.Softening point:n.a.Note:n.d.
boiling range: Sublimation point:n.a.Softening point:n.d.
Sublimation point:n.a.Softening point:n.d.
Softening point: n.d.
Flash point:- 24 °CDIN EN ISO 3679
Flammability
Solid/liquid: n.a.
Gas: n.a.



Schrader s.a.s.

according to UK REACH Regulation

	INNERLINER SEALER ONYX+	
Revision date: 22.11.2021	Product code: 12548-0011	Page 6 of 11
Explosive properties The product is considered non-ex	xplosive; nevertheless explosive vapour/air mixtu	ire can be generated
Lower explosion limits: Upper explosion limits:	1,0 vol. % 7,3 vol. %	,
Auto-ignition temperature:	413 °C	
Self-ignition temperature Solid: Gas:	n.a. n.a.	
Decomposition temperature:	n.d.	
Oxidizing properties Not oxidising.		
Vapour pressure: (at 20 °C)	150 hPa	*)
Density: Bulk density:	0,83 g/cm³ n.a.	
Water solubility: (at 20 °C)	Immiscible	
Solubility in other solvents n.d.		
Partition coefficient n-octanol/water:	n.d.	
Viscosity / dynamic:	6000 mPa·s	
Viscosity / kinematic: (at 40 °C)	> 20,5 mm²/s	
Flow time: (at 23 °C)	454 s	6 DIN EN ISO 2431
Relative vapour density:	n.d.	
Evaporation rate:	7,6	*)
Solvent separation test:	0 %	
Solvent content:	60 - 70 %	
9.2. Other information		

*) Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane, Hydrocarbons, C6, isoalkanes, < 3% n-hexane

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat. Vapour/air mixtures are explosive at intensive warming. Heating can release vapours which can be ignited.

10.5. Incompatible materials

oxidizing agents



according to UK REACH Regulation

INNERLINER SEALER ONYX+

Revision date: 22.11.2021

Product code: 12548-0011

Page 7 of 11

10.6. Hazardous decomposition products

No hazardous decomposition products known. Fire may produce: Carbon monoxide, carbon dioxide, sulphur oxides.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met. No toxicological data available. Naphtha (petroleum) LD50/oral/rat: > 2000 mg/kg LD50/dermal/rabbit: > 2000 mg/kg LC50/inhalation/rat: > 20 mg/l

Irritation and corrosivity

Causes skin irritation. Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Naphtha (petroleum) [Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane])

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Other information

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Contact with eyes may cause irritation.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available. Naphtha (petroleum) EC50/Daphnia: 1 - 10 mg/l EC50/Algae: 10 - 100 mg/l Zinc oxide EC50/Ceriodaphnia dubia/48 h = 0,01 - 0,1 mg/l EC50/Selenastrum capricornutum/72 h = 0,01 - 0,1 mg/l Toxic to aquatic life with long lasting effects.



according to UK REACH Regulation

INNERLINER SEALER ONYX+

Revision date: 22.11.2021

Product code: 12548-0011

Page 8 of 11

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Endocrine disrupting properties

No data available

12.7. Other adverse effects

Low hazard to waters.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Can be incinerated, when in compliance with local regulations. Where possible recycling is preferred to disposal.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number:</u>	UN 1133
14.2. UN proper shipping name:	ADHESIVES
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
	3
Classification code:	F1
Limited quantity:	5 L / 30 kg F1
Excepted quantity: Transport category:	3
Tunnel restriction code:	Ē



according to UK REACH Regulation

INNERLINER SEALER ONYX+

Revision date: 22.11.2021

Product code: 12548-0011

Page 9 of 11

Other applicable information (land transport) Receptacle max. 450 L, ADR subsection 2.2.3.1.4 HAZCHEM: 3YE

Inland waterways transport (ADN)	
<u>14.1. UN number:</u>	UN 1133
14.2. UN proper shipping name:	Adhesives
14.3. Transport hazard class(es):	3
14.4. Packing group:	111
Hazard label:	3
Classification code:	F1
Limited quantity:	5 L / 30 kg
Excepted quantity:	E1
Marine transport (IMDG)	
<u>14.1. UN number:</u>	UN 1133
14.2. UN proper shipping name:	ADHESIVES
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Marine pollutant:	Yes
Limited quantity: Excepted quantity:	5 L / 30 kg E1
EmS:	F-E, S-D
Other applicable information (marine Receptacle max. 450 L, IMDG Code	e transport)
Air transport (ICAO-TI/IATA-DGR)	
<u>14.1. UN number:</u>	UN 1133
14.2. UN proper shipping name:	ADHESIVES
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3
Limited quantity Passenger:	10 L
Passenger LQ:	Y344
Excepted quantity:	E1
IATA-packing instructions - Passenger:	
IATA-max. quantity - Passenger: IATA-packing instructions - Cargo:	
IATA-packing instructions - Cargo: IATA-max. quantity - Cargo:	



according to UK REACH Regulation

INNERLINER SEALER ONYX+

Revision date: 22.11.2021

Product code: 12548-0011

Page 10 of 11

Other applicable information (air transport) *) [3.3.3.1 IATA DGR]

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex X) Entry 28	/II):
2004/42/EC (VOC):	< 70 %
Information according to 2012/18/EU (SEVESO III):	P5c FLAMMABLE LIQUIDS
Additional information:	E2
National regulatory information	
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Water hazard class (D):	1 - slightly hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,6,7,11,12.

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk



according to UK REACH Regulation

INNERLINER SEALER ONYX+

Revision date: 22.11.2021

Product code: 12548-0011

Page 11 of 11

GHS = Globally Harmonized System of Classification and Labelling of Chemicals REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

'The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)